

OFT 1 Flat Roof Vent/Terminal

Product features and benefits

- Large free vent area/Low Pa resistance

Application

- Allows termination through a flat roof to ducting up to 166mm
- With the spigot cut to 50mm allows ventilation into a flat roof to meet the requirements of

Material Per Roof Type

- Asphalt: Polyethylene/Aluminium
- Felt: Polyethylene
- EPDM: Polyethylene/Aluminium/EPDM
- Bitumen: Polyethylene/Aluminium/Bitumen
- PVC: Polyethylene/Aluminium/PVC
- Polyethylene material is fire retardant

Colours

- Black (Stack section only)



Product Codes

	Asphalt	Felt	EPDM	Bitumen	PVC
OFT1 110mm	169931	169931	-	-	-
OFT1 131mm		-	185673	185675	185677
OFT1 166mm		169933 *	185690	185692	185694

* 169933 has a 160mm diameter

Weights

	Asphalt	Felt	EPDM	Bitumen	PVC
OFT1 110mm	1.06 kg	1.72kg	-	-	-
OFT1 131mm		-	1.53 kg	2.15 kg	1.56 kg
OFT1 166mm		2.4 kg	2.46 kg	3.09 kg	2.51 kg

Dimensions and Performance

Diameter	Height Above Roof	Flange Dia	Depth Below Roof	Free vent area	* Pa Resistance
mm	mm	mm	mm	mm ²	Extract
110mm	220	330	600	8,400	5.9
131mm	500	450	350	12,000	1.1
166 mm	522	450	350	18,750	1.0
160mm	240	363	600	18,750	3.0

- 131/110 reducer (147059)
- 131/125 reducer (147062)
- 167/149 reducer (147064)

NB Reducers available

Ubbink UK Ltd. – Phone: 01604 433 000 - www.ubbink.co.uk